

CB PRIMER

UNIVERSAL PRIMER

APPLICATIONS

Special primer and adhesive for absorbent and non-absorbent bases both on walls and floors. To strengthen and to obtain an optimal adhesion.

CHARACTERISTICS

- Reinforces the substrate and reduces suction
- Solvent-free
- Very high adhesion
- Fast drying
- Outdoor and indoor applications

INSTRUCTIONS FOR USE

The substrate must be sufficiently load-bearing and free of dirt, grease, dust and other contaminants. Remove substrates with insufficient load-bearing capacity. Dilute **CB Latex** in a ratio of 1 part **CB Latex** to 4 parts water. Apply **CB Latex** immediately with a roller or brush, thinly and without puddles. Except for objects with a specific drying time, work can be continued after approx 2 hours. Clean tools with water after use. Remove cured product with solvents or paint strippers.

CONSUMPTION

Ca 30-150 g/m² (according to the application)

PACKAGING

Plastic cans of 5 and 25 liters

SHELF LIFE

In the original, closed packaging, can be kept for at least 12 months if stored in a dry, frost-free place.

CONSIDERATION - EPILOGUE

The information in this technical sheet is based on extensive research and experience. However, the information is provided without any guarantee - directly implied - as to its correctness. The conditions or methods of handling, storage, use of the product are beyond our control and may also be beyond our knowledge. For these and other reasons, we accept no liability for damage or nuisance of any kind, caused by the use of the product in question. The indicated characteristics and properties are average values and analyses obtained at 20 °C, deviations are tolerated. The rewrite of this sheet replaces all previous sheets.