

CB FLOORSEALER FS

HIGH-PERFORMANCE PROTECTIVE FINISH FOR MINERAL SUBSTRATES

APPLICATION

CB Floorsealer FS was developed for the durable and qualitative protection of mineral substrates such as concrete floors, cement based screeds, screeds, quartz carpet floors, natural stone, clinker etc....

PRODUCT DESCRIPTION

CB Floorsealer FS is a solvent-free sealer based on 100% active, functional polymer technology.

CHARACTERISTICS

- Yellow, low-viscosity liquid
- Solvent-free
- Plasticizer-free
- Moisture-curing
- Suitable for alkaline substrates
- Application temperature: from +10 °C to +30 °C
- Hardens without addition of catalyst

USER INSTRUCTIONS

Total consumption: approx. 80-100 g/m² (two layers).

Consumption may vary depending on the absorbency of the substrate. To be applied with short hair roller or mop (suited for varnish).

Transparent finish: first apply two layers *CB Prime AB*, then finish with two layers **CB Floorsealer FS**.

TRANSPORT AND STORAGE

Transport and store away from frost. Protect the product and its packaging against direct sunlight. Avoid storage at temperatures <5°C and >30°C

CB Floorsealer FS should be stored in a dry room and outside the sun. Shelf life is limited to 1 year.

PACKAGING

Plastic jerrycans of 5 and 25L

CONSIDERATION - EPILOGUE

The information in this technical sheet is based on extensive research and experience. However, the information is provided without any guarantee - directly implied - as to its correctness. The conditions or methods of handling, storage, use of the product are beyond our control and may also be beyond our knowledge. For these and other reasons, we accept no liability for damage or nuisance of any kind, caused by the use of the product in question. The indicated characteristics and properties are average values and analyses obtained at 20 °C, deviations are tolerated. The rewrite of this sheet replaces all previous sheets.