

CB QUARTZ

DRIED QUARTZ MIXTURE FOR THE POLISHING OF CONCRETE FLOORS

APPLICATION

CB Quartz is used for polishing freshly poured concrete, to compact it and provides a strong, wear-resistant surface layer.

CHARACTERISTICS

Polishing sand consists of a mixture of dried quartz of 0.2-2m, cement and other additives.

- Easy in use
- Constant quality
- Strong and longwearing top layer

WORK METHOD

The **CB Quartz** mixture is sprinkled onto the concrete as soon as it can be walked on.

Spread this mixture over the wet floor

Afterwards you can polish the floor manually or with a polisher until the top layer has mixed with the present mushy layer of the concrete.

After achieving the desired result of the concrete floor, it is advisable to treat it with *CB Curing TR* to prevent it from drying out prematurely.

CONSUMPTION

Manual spreading	: 1 à 3 kg/m ²
Mechanical spreading	: 2 à 3 kg/m ²

PACKAGING

25kg bags

SHELF LIFE, TRANSPORT & CONSERVATION

1 year after manufacture in the original, closed packaging.

Frost-free transport and storage. Protect the product and its packaging from direct sunlight. Avoid storage at temperatures >30°C.

CONSIDERATION - EPILOGUE

The information in this technical sheet is based on extensive research and experience. However, the information is provided without any guarantee - directly implied - as to its correctness. The conditions or methods of handling, storage, use of the product are beyond our control and may also be beyond our knowledge. For these and other reasons, we accept no liability for damage or nuisance of any kind, caused by the use of the product in question. The indicated characteristics and properties are average values and analyses obtained at 20 °C, deviations are tolerated. The rewrite of this sheet replaces all previous sheets.