

CB CURING TR

TRANSPARENT AND WATER CLEAR CURING COMPOUND FOR INDUSTRIAL FLOORING AND COLORED CONCRETE

APPLICATION

CURING TR is a curing compound for aesthetic concrete surfaces that in there “plastic” phase are submitted to atmospheric conditions.

DESCRIPTION

CURING TR is a curing compound based on a selection of resin which, 20 minutes after application, forms a thin water damp barrier. By this, the risk of plastic shrinking cracks is drastically reduced and the properties of the concrete are optimized. **CURING TR** does not affect the aesthetic aspect of the concrete. **CURING TR** protects against a premature drying out of the concrete due to a serious diminution of waterloos, caused by a combination of sunrays, low relative humidity and wind

CHARACTERISTICS

Form	: Liquid
Color	: Transparent
Density	: 0,82kg/ltr

USER INSTRUCTIONS

Apply **CURING TR** homogeneous, just after evaporation of the “bleeding” water. **CURING TR** is easy to spray on.

CONSUMPTION – SHELF LIFE

+/- 0,100 - 0,120 ltr/m²

If stored in a dry place, protected from moisture and frost, in the original packaging, keep for at least 12 months.

PACKAGING

25 liter, 10 liter & 1000 liter

CONSIDERATION - EPILOGUE

The information in this technical sheet is based on extensive research and experience. However, the information is provided without any guarantee - directly implied - as to its correctness. The conditions or methods of handling, storage, use of the product are beyond our control and may also be beyond our knowledge. For these and other reasons, we accept no liability for damage or nuisance of any kind, caused by the use of the product in question. The indicated characteristics and properties are average values and analyses obtained at 20 °C, deviations are tolerated. The rewrite of this sheet replaces all previous sheets.

