

# CB BELAX

## BIODEGRADABLE UNIVERSAL FORMWORK MATERIAL WITH EXCELLENT VISIBLE CONCRETE PROPERTIES

### APPLICATIONS

- Closures
- Beams and columns
- Walking elements, cellars, casting walls

### DESCRIPTION

The formwork removal agent BELAX 2 contains only aromatics-free and mineral base oils, as well as rapidly biodegradable additives. BELAX 2 contains no volatile solvents (V.O.S.). BELAX 2 is used undiluted. BELAX 2 can be used for suction and non-suction formwork in wood, steel and plastic.

### TECHNICAL DATA

Density	: 20°C : 0,87 kg/l (iso 3675)
Viscosity 40 °C	: > 7 mm <sup>2</sup> /sec (iso3104)
Colour	: light yellow
Odour	: almost odourless
Flash point	: > 100 °C
Volatile Organic Compounds	: no emission up to 25 °C
R-phrases	: none
Aromatics	: <0.02

### INSTRUCTION MANUAL

BELAX 2 is preferably applied with a spray nozzle or roller. Make sure that the product is applied in an even film to avoid staining and excessive use.

### CONSUMPTION – PACKAGE – SHELF LIFE

+/- 0,150 kg/m<sup>2</sup>

30 liters & 1000 liters

If stored in a dry place, protected from moisture and frost, in the original packaging, keep for at least 12 months.

### CONSIDERATION - EPILOGUE

The information in this technical sheet is based on extensive research and experience. However, the information is provided without any guarantee - directly implied - as to its correctness. The conditions or methods of handling, storage, use of the product are beyond our control and may also be beyond our knowledge. For these and other reasons, we accept no liability for damage or nuisance of any kind, caused by the use of the product in question. The indicated characteristics and properties are average values and analyses obtained at 20 °C, deviations are tolerated. The rewrite of this sheet replaces all previous sheets.